



HIGH FREQUENCY GENERATORS

► 900 HI-PE series



FEATURES / BENEFITS

- Dual Alternate, high Power output
- High level of performance with minimal operating costs
- Very compact and integrable Generators
- Miniaturized Heating Heads
- High Safety: all models output isolated from the mains
- Continuous generation
- Built-in Self-diagnosis
- Maintains stable and accurate output power even as working conditions change
- Supplied with Calibration Certificate
- Digital and analog control of the output power
- Interfaces with CEIA Master Controller V3+ unit to manage heating cycles (temperature, time and power)
- Compliant with the Regulations on Electrical Safety and Electromagnetic Compatibility



www.ceia.net

CEIA reserves the right to make changes, at any moment and without notice, to the models (including programming), their accessories and options, to the prices and conditions of sale



900 HI-PE SERIES HIGH FREQUENCY GENERATORS



The 900 HI-PE series of High Frequency Generators spans five models with a power rating range of 2.8 to 6kW. They combine the miniaturized CEIA Heating Head solution [patented] with a powerful, continuous-duty rated generator with so high efficiency that it can replace traditional generators in applications up to 12kW, thus cutting the initial investment and operating costs.

These compact devices are manufactured using solid-state technology and each has an embedded microprocessor. This guarantees stable power output as well as optimum operating frequency. The microprocessor also performs monitoring and diagnostic functions to inform the user of device status.

The generators have an ideal design for integration into automatic production systems. Space efficiency and simple operation also make these generators perfect for manual applications. All CEIA Power Cube Generators can be combined with the CEIA Master Controller V3+ unit.

They can even be interfaced with PCs or programmable controllers via their analog and RS-232 interfaces. Each HI-PE Generator is accompanied by a calibration report that certifies the stability of the output voltage coming from the heating head.

The use of innovative technology and latest-generation components places the 900 series generators in a class of their own in terms of performance, power output and operational cost.

		32/1800	32/900	45/900	64/900	90/900
INPUT / OUTPUT	Maximum absorbed power	2.8 kW	2.8 kW	3.5 kW	5.6 kW	6 kW
	Average output power at inductor	32 kVAR	32 kVAR	45 kVAR	64 kVAR	90 kVAR
	Available outputs	Two, alternate				
	Supply voltage	180... 260 Vac 1~ 50/60 Hz				400 Vac $\pm 10\%$ 3/PE~ 50/60 Hz
	Water cooling	Pressure: 300 kPa Flow: 1.5 - 2.0 l/min for each head connected			Pressure: 300 kPa Flow: 4.0 - 5.0 l/min for each head connected	
INTERFACE INPUT/OUTPUT	RS232 serial interface	Standard				
	Digital input activator	Two, one per each output power - Standard				
	Analogue power adjustment input	Option, on request				Standard
OPERATING CONDITIONS	Operating temperature	+ 5 to + 55°C				
	Storage temperature	- 25 to + 70 °C				
	Relative humidity	0 ÷ 95 % (without condensation)				
FREQUENCY RANGE	1300 kHz... 1800 kHz	750 kHz... 1150 kHz				
DIMENSIONS IN mm (WxDxH)	Generator	275 x 265 x 140			275 x 265 x 280	445 x 287 x 132
	Heating head HH10/HH11	62,5 x 123 x 95 (HH10)				
	Miniaturized heating head HH15	52 x 75.5 x 77			Not applicable	
	Standard inductor holder	100	150		65	
WEIGHT	Generator	10 kg			20 kg	
	Heating head	1,3 kg (HH15) - 1,6 kg (HH10)			2,2 kg (HH11)	3 kg (HH12)
CONFORMITY	Complies with international standards currently applicable for Electrical Safety (EN 60204-1) and Electromagnetic Compatibility (EN 61000-6-2)					



HEATING HEAD HH10/HH11
FOR POWER CUBE 32/45/64, MOUNTED ON
POSITIONING BASE ES35

* Inductors shown in the pictures as example only

**MINIATURIZED
HEATING HEAD HH15**
FOR POWER CUBE 32/45



COSTRUZIONI ELETTRONICHE INDUSTRIALI AUTOMATISMI

Zona Ind.le 54/G, 52041 Vicinaggio - AREZZO (ITALY)

Tel. +39 0575-4181 • Fax +39 0575-418287 • E-mail: powercube@ceia-spa.com

www.ceia.net

CEIA reserves the right to make changes, at any moment and without notice, to the models (including programming), their accessories and options, to the prices and conditions of sale - DP040K0001v3000hUK-67307

